



ZA16A

**1.6 tons mini excavators
with heated cab
or canopy**





Sticker Price : \$17,390.00

Discount : 12.00 % OFF

Discounted Price : \$15,303.20

Machinery Assets

- Kubota D722 engine
- 380mm bucket with teeth
- Swing boom
- Canopy or heated cab
- Rubber Truck
- H/L speed
- Auxiliary hydraulic Pipeline
- Two year warranty

Extended Warranty

- 3 years or 3000 hours(+\$459.00)
- 4 years or 4000 hours(+\$767.00)
- 5 years or 5000 hours(+\$1,377.00)

Factory Options

- Canopy
- Heated Cabin(+ \$1,050.00)
- Hydraulic Thumb(+ \$780.00)
- Quick Hitch Aux Pipeline(+ \$300.00)

Machinery Accessories

- Mechanical quick hitch (+\$150.00)
- Hydraulic Quick Hitch (+\$440.00)
- 200 mm Bucket with Teeth (+\$165.00)
- 260 mm Bucket with teeth (+\$198.00)
- 800 mm Clean Bucket (+\$184.80)
- 800 mm Hydraulic Tilt Bucket (+\$550.00)

Machine Specification

Machinery Size		Tech. Specifications		Working Range	
(mm) Total Length	3335	(l³/mm) Standard Bucket Capacity/Length	0.025/380	(mm) Max. Digging Height	2961
(mm) Total Width	990/1300	(rmp) Swing Speed	1-13	(mm) Max. Dumping Height	2083
(mm) Track Width	200	(°) Gradeability	30	(mm) Max. Digging Depth	1953
(kg) Machine Weight (with all fluids)	1530	(KN) Max. Bucket Digging Force	9	(mm) Max. Vertical Digging Depth	1859
(mm) Canopy Height	2270	(KN) Max. Arm Digging Force	5.5	(mm) Max. Digging Radius	3519
(mm) Axle Base	1215	Engine Model	KUBOTA D722	(mm) Max. Swing Radius	-
(mm) Wheel (track) Distance	790	(Kw(HP)/rpm) Power/Revolution speed	10.2[13.8]/2500	(mm) Max. Dozer Blade Lifting Distance	224
(mm) Minimum Ground Clearance	153	(MPa) System Pressure	17	(mm) Max. Dozer Blade Cutting Distance	237
(mm) Tail Swing Radius	655	(L) Fuel Tank Capacity	14.5		
		(L) Hydraulic Circuit Capacity	21		
		(L) Cooling Circuit Capacity	5		
		(L) Engine Oil Capacity	2.5		
		(m³) Bucket capacity	0.025		

